

400 Seventh Street, S.W. Washington, D.C. 20590

MAR 1 7 2004

Research and Special Programs Administration

DOT-E 6293 (ELEVENTH REVISION)

EXPIRATION DATE: February 28, 2006

(FOR RENEWAL, SEE 49 CFR § 107.109)

ATK Aerospace Company, Inc. 1.

(Former Grantee: Alliant Techsystems, Inc.)

Salt Lake City, UT

(See Appendix A to this document for a list of additional grantees)

PURPOSE AND LIMITATION: 2.

- This exemption authorizes the transportation in commerce of spent mixed acid containing not over 3% dissolved nitroglycerin, not over 16% nitric acid, and at least 18% water by volume, in stainless steel DOT specification cargo tanks. This exemption provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
- The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce.
- REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-3. 180.
- REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.56(b) in that 4. mixtures are not required to be examined, classed and approved, except as specified herein.
- This exemption is based on the application of ATK 5. Aerospace Company, Inc., dated February 12, 2004, submitted in accordance with § 107.109.

HAZARDOUS MATERIALS (49 CFR § 172.101): 6.

Proper Shipping Name/ Hazardous Materials Description	Hazard Class/ Division	Identi- fication Number	Packing Group
Nitrating acid mixtures, spent with not more than 50 percent nitric acid	8	UN1826	II

7. SAFETY CONTROL MEASURES:

- PACKAGING Packagings prescribed are insulated stainless steel DOT Specification MC-311 or MC-312 or DOT-412 cargo tank motor vehicles, equipped for top loading and unloading only. The cargo tank design pressure may not be less than 30 psig.
- TESTING Each cargo tank motor vehicle must be reinspected and retested as specified in § 180.407 for MC-311, MC-312, and DOT-412 cargo tank motor vehicles.

OPERATIONAL CONTROLS -

- During transportation, the temperature of the lading must be maintained between 40°F and 80°F.
- Before each shipment, a spent acid analysis must be made. A copy of each analysis must be kept on file and be available for examination by representatives of the Department for at least three months after shipment. PRIMEX Technologies, Inc. must file reports of the analyses performed on the spent acid in the first six shipments with the Office of Hazardous Materials Exemptions and Approvals (OHMEA). Reports on whether the nitroglycerin was still completely in solution after the acid was transported must be filed with OHMEA.
- (3) Each cargo tank must be operated in exclusive use service while transporting only the spent acid provided for herein, sulfuric acid, spent (UN1832) or nitrating acid mixtures (UN1796).

8. SPECIAL PROVISIONS:

- a. A person who is not a holder of this exemption who receives a package covered by this exemption may reoffer it for transportation provided no modifications or changes are made to the package and it is reoffered for transportation in conformance with this exemption and the HMR.
- b. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.
- c. MARKING Each cargo tank motor vehicle must be plainly marked on the right side near the front, in letters at least two inches high on a contrasting background, "DOT-E 6293". Additionally, cargo tank motor vehicles specified herein marked "DOT SP 6293" prior to the issuance of the exemption may be transported under the terms of this exemption.
- 9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle.
- 10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each motor vehicle used to transport packages covered by this exemption.
- 11. <u>COMPLIANCE</u>: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
 - O All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Persons operating under the terms of this exemption must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incident involving the package and shipments made under the terms of this exemption.

Issued in Washington, D.C.:

Robert A. McGuire

Associate Administrator for Hazardous Materials Safety

MAR 1 7 2004

(DATE

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590. Attention: DHM-31.

Copies of this exemption may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/exemptions Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

PO: sln

MAR 1 7 2004

The following are hereby granted party status to this exemption based on their application(s) submitted in accordance with § 107.107 or § 107.109, as appropriate:

Company Name	Application	Issue	Expiration
City/State	Date	Date	Date
Dyno Nobel, Inc.	Feb 26,	MAR 1 7 2004	Feb 28,
Salt Lake City, UT	2004		2006
St. Marks Powder, Inc. St. Marks, FL	Jan 21, 2004	MAR 1 7 2004	Feb 28, 2006

Associate Administrator for Hazardous Materials Safety MAR 1 7 2004